

Silicon Bridge Rectifiers

FTDF40K - FTDF40M

Features

- Glass passivated junction
- High surge current capability
- Saves space on printed circuit boards
- High soldering temperature guaranteed: 260°C @ 10s
- RoHS compliant with Halogen-free



Mechanical Data

- Low profile saves space on printed circuit boards
- Molding compound, UL flammability classification rating 94V-0
- Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102
- Polarity: As marked on body

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	FTDF40K	FTDF40M	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	800	1000	V
RMS Reverse Voltage	V _{RMS}	560	700	V
DC Blocking Voltage	V _{DC}	800	1000	V
Average Forward Output Current	I _{F_AV}	4.0		A
Peak Forward Surge Current, 8.3ms Single Half-Sine-wave	I _{FSM}	100		A
I ² t Rating for fusing	I ² t	41.5		A ² s

Thermal Characteristics

Parameter	Symbol	FTDF40K	FTDF40M	Unit
Typical Thermal Resistance *1	R _{ΘJA}	50		°C/W
	R _{ΘJC}	10		
Operating Junction Temperature Range	T _J	-55 ~ +150		°C
Storage Temperature Range	T _{STG}	-55 ~ +150		°C

Note *1: Device mounted on PCB with 10 mm x 20 mm x 0.1mm copper pad areas

Silicon Bridge Rectifiers

FTDF40K - FTDF40M

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Typ.	Max.	Unit
Instantaneous Forward Voltage	V_F	$I_F = 4.0\text{A}$ Per Diode	-	1.3	V
Reverse Current	I_R	Rated V_R	@ $T_A = 25^\circ\text{C}$	10	μA
			@ $T_A = 125^\circ\text{C}$	200	
Reverse Recovery Time	t_{rr}	$I_F=0.5\text{A}, I_{RM}=1\text{A},$ $I_{R(REC)}=0.25\text{A}$	-	500	ns

Silicon Bridge Rectifiers

FTDF40K - FTDF40M

Ratings and Characteristic Curves (@T_A=25°C unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Surge Current Derating Curve




Fig.3 Typical Forward Voltage Characteristics






Fig.4 Typical Reverse Characteristics




Silicon Bridge Rectifiers

FTDF40K - FTDF40M

Package Outline Dimensions (unit: mm)



Mounting Pad Layout (unit: mm)



Ordering Information

Part Number	Marking	Package	Shipping Quantity
FTDF40K	FTDF40K	TDF	3000 / Tape & Reel
FTDF40M	FTDF40M	TDF	3000 / Tape & Reel